Seismic Zone/

**CODES** 



## **Mechanical Anchors Inspection Checklist for Concrete and Masonry**

Periodic special must be performed where required in accordance with Section 1705.1.1 and Table 1705.3 of the 2012 IBC, or Section 1704.15 of the 2009 IBC and Table 1704.4 or Section 1704.13 of the 2006 or 2003 IBC, whereby periodic special inspection is defined in Section 1702.1 of the IBC and this report. (See Structural Drawings for Inspection requirements)

Project Name:			□ IBC 2003	Seismic Design Category
Project Location:			☐ IBC 2006 ☐ IBC 2009	
Weather:	Air Temperature:	(°F/°C)	☐ IBC 2012	
Lot No.: ICC-ES Report No.: Head Configuration: F Diameter/Dimension: 1		ead □Torque Cap		
Aateri □ Otl	/ Concrete			ζ
Drill Bit Diameter: (in/mm)  Hole Depth: (in/mm)  Drill Bit Type: Carbide-Tip Drill Bit Diamond Core Bit Other  (ANSI B212.15-1994) Diamond Core Bit Other  Hole Cleaning: Compressed Air Hand Pump Wire Brush Other  Hole Condition: Dry Water Saturated				
Anchor Spacing:	Overhead	h <sub>ef</sub>		
Completed by:			:/ pany:	