

HIT-RE 500 V4

Safety information for 2-Component-products

Issue date: 10/02/2021

Revision date: 10/02/2021

Version: 1.0

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-RE 500 V4



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti Saudi Arabia for Construction Tools LLC
King Fahd Street
P.O. Box 15930
21454 Jeddah - Saudi Arabia
T +966 2 213 8400 - F +966 2 697 4696
sa.customerservice@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3:

Classification of the Product

Classification according to the United Nations GHS (Rev. 4, 2011)

Acute Tox. 5 (Oral)	H303
Skin Corr. 1B	H314
Skin Sens. 1	H317
Muta. 2	H341
Repr. 1B	H360
STOT SE 3	H335
Aquatic Acute 2	H401
Aquatic Chronic 2	H411

Label elements

Labelling according to the United Nations GHS (Rev. 4, 2011)

Hazard pictograms (GHS UN)



GHS05



GHS07



GHS08



GHS09

Signal word (GHS UN)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS UN)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H335 - May cause respiratory irritation.

HIT-RE 500 V4


Safety information for 2-Component-products

Precautionary statements (GHS UN)

H341 - Suspected of causing genetic defects.
H360 - May damage fertility or the unborn child.
H411 - Toxic to aquatic life with long lasting effects.
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

Additional information

2-component-foilpack, contains:
Component A: Epoxy resin, Reactive diluent, inorganic filler
Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	Classification according to the United Nations GHS
HIT-RE 500 V4, A		1	pcs	Skin Corr. 1C, H314 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
HIT-RE 500 V4, B		1	pcs	Acute Tox. 5 (Oral), H303 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters
Notify authorities if liquid enters sewers or public waters
Avoid release to the environment
Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.
After curing, the product can be disposed of with household waste.

Storage conditions

Protect from sunlight. Store in a well-ventilated place.

Technical measures

Comply with applicable regulations

Precautions for safe handling

Wear personal protective equipment
Avoid contact with skin and eyes
Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
Avoid contact during pregnancy/while nursing

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation
Mechanically recover the product
On land, sweep or shovel into suitable containers
Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition

HIT-RE 500 V4

Safety information for 2-Component-products

Incompatible products	Direct sunlight Strong bases Strong acids
-----------------------	---

SECTION 6: First aid measures

First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after ingestion	Do not induce vomiting Rinse mouth Immediately call a POISON CENTER/doctor.
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures general	Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	Causes serious eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Issue date: 10/02/2021 Revision date: 10/02/2021

Version: 1.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form	Mixture
Product name	HIT-RE 500 V4, B
UN-No. (ADR)	3259
Product code	Bu Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended uses and restrictions	For professional users only

1.4. Supplier's details

Supplier

Hilti Saudi Arabia for Construction Tools LLC
King Fahd Street
P.O. Box 15930
21454 Jeddah - Saudi Arabia
T +966 2 213 8400 - F +966 2 697 4696
sa.customerservice@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum – 24h Service +41 44 251 51 51 (international) +966 2 213 8400
------------------	--

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Acute toxicity (oral), Category 5	H303	Calculation method
Skin corrosion/irritation, Category 1B	H314	Expert judgment
Skin sensitisation, Category 1	H317	Calculation method
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335	Calculation method
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Calculation method
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Calculation method

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)



GHS05



GHS07

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Signal word (GHS UN)	Danger
Hazardous ingredients	2-methyl-1,5-pentanediamine; Phenol, styrenated; m-Xylylenediamine; 3-Aminopropyltriethoxysilan; 2,4,6-tris(dimethylaminomethyl)phenol
Hazard statements (GHS UN)	H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H335 - May cause respiratory irritation H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS UN)	P262 - Do not get in eyes, on skin, or on clothing. P280 - Wear eye protection, protective clothing, protective gloves. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice, medical attention. P337+P313 - If eye irritation persists: Get medical advice, medical attention. P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
2-methyl-1,5-pentanediamine	(CAS-No.) 15520-10-2	25 - 35	Flammable liquids, Category 4, H227 Acute toxicity (oral), Category 4, H302 Acute toxicity (dermal), Category 4, H312 Acute toxicity (inhalation:dust,mist) Category 4, H332 Skin corrosion/irritation, Category 1A, H314 Serious eye damage/eye irritation, Category 1, H318 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation, H335
Phenol, styrenated	(CAS-No.) 61788-44-1	5 - 10	Skin corrosion/irritation, Category 2, H315 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 2, H401 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
m-Xylylenediamine	(CAS-No.) 1477-55-0	5 - <8	Flammable liquids Not classified Acute toxicity (oral), Category 4, H302 Acute toxicity (inhalation:dust,mist) Category 4, H332 Skin corrosion/irritation, Category 1B, H314 Serious eye damage/eye irritation, Category 1, H318 Skin sensitisation, category 1B, H317 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402 Hazardous to the aquatic environment — Chronic Hazard, Category 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2	1 - 2,5	Flammable liquids Not classified Acute toxicity (oral), Category 4, H302 Skin corrosion/irritation, Category 2, H315

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

			Serious eye damage/eye irritation, Category 2A, H319 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402
3-Aminopropyltriethoxysilan	(CAS-No.) 919-30-2	1 - 2,5	Acute toxicity (oral), Category 4, H302 Skin corrosion/irritation, Category 1B, H314

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Special protective actions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and materials for containment and cleaning up

For containment Collect spillage.
Methods for cleaning up This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.
Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Comply with applicable regulations.
Storage conditions Protect from sunlight. Store in a well-ventilated place.
Incompatible products Strong bases. Strong acids.
Incompatible materials Sources of ignition. Direct sunlight.
Heat and ignition sources Keep away from heat and direct sunlight.
Storage temperature 5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls Ensure good ventilation of the work station.
Environmental exposure controls No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.
Consumer exposure controls Avoid contact during pregnancy/while nursing.
Other information Do not eat, drink or smoke during use.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing Long sleeved protective clothing
Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

Eye protection Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection Wear suitable protective clothing

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste
Colour	red.
Odour	Amine-like.
Odour threshold	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Flammability (solid, gas)	Non flammable.
Explosive limits	Not applicable
Lower explosive limit (LEL)	Not applicable
Upper explosive limit (UEL)	Not applicable
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
pH	Not available
pH solution	Not available
Viscosity, kinematic (calculated value) (40 °C)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	Not available
Vapour pressure at 50 °C	Not available
Density	1.31 g/cm ³
Relative density	Not available
Relative vapour density at 20 °C	Not applicable
Solubility	insoluble in water.
Viscosity, dynamic	50 – 70 Pa·s HN-0333
Particle size	Not available

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Particle size distribution	Not available
Particle shape	Not available
Particle aspect ratio	Not available
Particle specific surface area	Not available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive vapours.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	May be harmful if swallowed.
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

ATE UN (oral)	2786.216 mg/kg bodyweight
---------------	---------------------------

2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
LD50 dermal rat	1870 mg/kg
LC50 Inhalation - Rat	4.9 mg/l
Phenol, styrenated (61788-44-1)	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	158.31 mg/l/4h
m-Xylylenediamine (1477-55-0)	
LD50 oral rat	1090 mg/kg
LD50 oral	660 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1.34 mg/l/4h
3-Aminopropyltriethoxysilan (919-30-2)	
LD50 oral rat	1.57 ml/kg
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/irritation	Assumed to cause serious eye damage
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Harmful to aquatic life.
Classification procedure (Hazardous to the aquatic environment, short-term (acute))	Calculation method
Hazardous to the aquatic environment, long-term (chronic)	Harmful to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic))	Calculation method

2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 fish 1	130 mg/l (LC50; 48 h)
LOEC (acute)	1800 mg/l
NOEC (acute)	1000 mg/l
Phenol, styrenated (61788-44-1)	
LC50 fish 1	5.6 mg/l
LC50 other aquatic organisms 1	9.7 mg/l
EC50 Daphnia 1	1.44 mg/l
EC50 72h algae (1)	0.326 mg/l (Algae, Literature study)
NOEC (acute)	3.2 mg/l
Threshold limit algae 1	0.326 mg/l (72 h; Algae)
Threshold limit algae 2	0.14 mg/l (72 h; Algae)
m-Xylylenediamine (1477-55-0)	
LC50 fish 1	75 mg/l
LC50 other aquatic organisms 1	20.3 ppb
EC50 Daphnia 1	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 fish 1	> 100 mg/l (96 h; Pisces; Nominal concentration)
LC50 fish 2	70.9 mg/l (96 h; Pisces)
EC50 other aquatic organisms 1	84 mg/l (72 h; Desmodesmus subspicatus; growth rate; ECHA)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)
Threshold limit algae 1	10 - 100, Algae
Threshold limit algae 2	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)

HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

12.2. Persistence and degradability

HIT-RE 500 V4, B	
Persistence and degradability	May cause long-term adverse effects in the environment.
Phenol, styrenated (61788-44-1)	
Biochemical oxygen demand (BOD)	0.000231 g O ₂ /g substance
Chemical oxygen demand (COD)	0.004827 g O ₂ /g substance
m-Xylylenediamine (1477-55-0)	
Not rapidly degradable	

12.3. Bioaccumulative potential

HIT-RE 500 V4, B	
Bioaccumulative potential	Not established.
2-methyl-1,5-pentanediamine (15520-10-2)	
Partition coefficient n-octanol/water (Log Kow)	0.27 (Estimated value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Phenol, styrenated (61788-44-1)	
BCF fish 2	3246 mg/l
Partition coefficient n-octanol/water (Log Kow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
Bioaccumulative potential	Bioaccumulative potential.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Kow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

HIT-RE 500 V4, B	
Mobility in soil	No additional information available
Phenol, styrenated (61788-44-1)	
Ecology - soil	No (test)data on mobility of the substance available.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Koc)	1.32 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.





HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 3259	UN 3259	UN 3259	UN 3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
14.3. Transport hazard class(es)			
8	8	8	8
			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	2
Orange plates	



Tunnel restriction code (ADR)	E
-------------------------------	---

Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002



HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
MFAG-No	154
Air transport	
PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3
Rail transport	
Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

SDS Major/Minor	None
Issue date	10/02/2021
Revision date	10/02/2021



HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE - Acute Toxicity Estimate
BCF - Bioconcentration factor
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
IATA - International Air Transport Association
EC50 - Median effective concentration
IMDG - International Maritime Dangerous Goods
LC50 - Median lethal concentration
LD50 - Median lethal dose
LOAEL - Lowest Observed Adverse Effect Level
NOAEC - No-Observed Adverse Effect Concentration
NOAEL - No-Observed Adverse Effect Level
NOEC - No-Observed Effect Concentration
PBT - Persistent Bioaccumulative Toxic
PNEC - Predicted No-Effect Concentration
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS - Safety Data Sheet
vPvB - Very Persistent and Very Bioaccumulative

Other information

None.

Full text of H-statements:	
H227	Combustible liquid
H302	Harmful if swallowed
H303	May be harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS_UN_Hilti



HIT-RE 500 V4, B

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Issue date: 10/02/2021 Revision date: 10/02/2021

Version: 1.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form	Mixture
Product name	HIT-RE 500 V4, A
UN-No. (ADR)	1759
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended uses and restrictions	For professional users only

1.4. Supplier's details

Supplier

Hilti Saudi Arabia for Construction Tools LLC
King Fahd Street
P.O. Box 15930
21454 Jeddah - Saudi Arabia
T +966 2 213 8400 - F +966 2 697 4696
sa.customerservice@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum – 24h Service +41 44 251 51 51 (international) +966 2 213 8400
------------------	--

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Skin corrosion/irritation, Category 1C	H314	Calculation method
Skin sensitisation, Category 1	H317	Calculation method
Germ cell mutagenicity, Category 2	H341	Expert judgment
Reproductive toxicity, Category 1B	H360	Expert judgment
Hazardous to the aquatic environment — Acute Hazard, Category 2	H401	Calculation method
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411	Calculation method
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)



GHS05



GHS07



GHS08



GHS09

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Signal word (GHS UN)	Danger
Hazardous ingredients	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ; butanedioldiglycidyl ether ; 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; trimethylolpropane triglycidylether
Hazard statements (GHS UN)	H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H341 - Suspected of causing genetic defects H360 - May damage fertility or the unborn child H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (GHS UN)	P262 - Do not get in eyes, on skin, or on clothing. P280 - Wear eye protection, protective clothing, protective gloves. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice, medical attention. P337+P313 - If eye irritation persists: Get medical advice, medical attention. P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	(CAS-No.) 1675-54-3	25 – 40	Flammable liquids Not classified Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 2, H401 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5	10-20	Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
butanedioldiglycidyl ether	(CAS-No.) 2425-79-8	5 – 10	Acute toxicity (oral), Category 4, H302 Acute toxicity (dermal), Category 4, H312 Acute toxicity (inhal.), Category 4, H332 Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 1, H318 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402 Hazardous to the aquatic environment — Chronic Hazard, Category 3, H412
trimethylolpropane triglycidylether	(CAS-No.) 30499-70-8	5 – 10	Skin corrosion/irritation, Category 1C, H314 Serious eye damage/eye irritation, Category 1, H318 Skin sensitisation, category 1B, H317

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

			Germ cell mutagenicity, Category 2, H341 Reproductive toxicity, Category 1B, H360 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8	2.5 – 5	Acute toxicity (dermal), Category 5, H313 Serious eye damage/eye irritation, Category 1, H318 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Special protective actions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
6.1.1. For non-emergency personnel	
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Heat and ignition sources	Keep away from heat and direct sunlight.
Storage temperature	5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.
------------------------	--

8.2. Appropriate engineering controls

Appropriate engineering controls	No specific measures identified.
Environmental exposure controls	No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

8.3. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing

Long sleeved protective clothing

Hand protection

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

Eye protection

Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection

Wear suitable protective clothing

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste
Colour	Light grey.
Odour	characteristic.
Odour threshold	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Flammability (solid, gas)	Non flammable.
Explosive limits	Not applicable
Lower explosive limit (LEL)	Not applicable
Upper explosive limit (UEL)	Not applicable
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
pH	Not available
pH solution	Not available
Viscosity, kinematic (calculated value) (40 °C)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	Not available
Vapour pressure at 50 °C	Not available
Density	1.45 g/cm ³
Relative density	Not available

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Relative vapour density at 20 °C	Not applicable
Solubility	insoluble in water.
Viscosity, dynamic	45 – 59 Pa·s 23 °C
Particle size	Not available
Particle size distribution	Not available
Particle shape	Not available
Particle aspect ratio	Not available
Particle specific surface area	Not available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)
butanedioldiglycidyl ether (2425-79-8)	
LD50 oral rat	2980 mg/kg (Rat)
LD50 oral	1163 mg/kg (Rat; Exp. Key study ECHA)
LD50 dermal rabbit	1130 mg/kg (Rabbit)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/irritation	Assumed to cause serious eye damage

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Not classified
Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Toxic to aquatic life.
Classification procedure (Hazardous to the aquatic environment, short-term (acute))	Calculation method
Hazardous to the aquatic environment, long-term (chronic)	Toxic to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic))	Calculation method

butanedioldiglycidyl ether (2425-79-8)	
LC50 fish 1	24 mg/l (96 h; Pisces) ECHA
LC50 other aquatic organisms 1	> 160 mg/l
NOEC (acute)	40 mg/l
Threshold limit algae 1	88930 mg/l (96 h; Algae)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LC50 fish 1	55 mg/l (96 h; Cyprinus carpio; Young)
LC50 fish 2	237 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	473 – 710 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	119 mg/l (7 days; Anabaena flosaquae)
Threshold limit algae 2	250 mg/l (72 h; Selenastrum capricornutum)
2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)bisoxirane (1675-54-3)	
LC50 fish 1	1.2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
LC50 fish 2	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
EC50 Daphnia 1	1.7 mg/l
EC50 72h algae (1)	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
Threshold limit algae 1	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit algae 2	4.2 mg/l (72 h; Scenedesmus sp.)

12.2. Persistence and degradability

HIT-RE 500 V4, A	
Persistence and degradability	May cause long-term adverse effects in the environment.
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
Not rapidly degradable	
butanedioldiglycidyl ether (2425-79-8)	
Biochemical oxygen demand (BOD)	0.01982 g O ₂ /g substance

HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)
Not rapidly degradable
trimethylolpropane triglycidylether (30499-70-8)
Not rapidly degradable

12.3. Bioaccumulative potential

HIT-RE 500 V4, A	
Bioaccumulative potential	Not established.
butanedioldiglycidyl ether (2425-79-8)	
Partition coefficient n-octanol/water (Log Kow)	-0.15
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Partition coefficient n-octanol/water (Log Kow)	-0.92 (Estimated value)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
BCF other aquatic organisms 1	31 (Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Kow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

12.4. Mobility in soil

HIT-RE 500 V4, A	
Mobility in soil	No additional information available
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Partition coefficient n-octanol/water (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information





In accordance with ADR / IATA / IMDG / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 1759	UN 1759	UN 1759	UN 1759

HIT-RE 500 V4, A


Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

14.2. UN proper shipping name			
CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	Corrosive solid, n.o.s. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)
Transport document description			
UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1759 Corrosive solid, n.o.s. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
8	8	8	8
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	C10
Special provisions (ADR)	274
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR)

E

Transport by sea

Special provisions (IMDG)	223, 274
Packing instructions (IMDG)	P002, LP02
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A

Air transport

PCA packing instructions (IATA)	860
PCA max net quantity (IATA)	25kg
CAO packing instructions (IATA)	864
Special provisions (IATA)	A3, A803

Rail transport

Special provisions (RID)	274
--------------------------	-----



HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Packing instructions (RID)

P002, IBC08, LP02, R001

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

SDS Major/Minor

None

Issue date

10/02/2021

Revision date

10/02/2021

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE - Acute Toxicity Estimate

BCF - Bioconcentration factor

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DMEL - Derived Minimal Effect level

DNEL - Derived-No Effect Level

IATA - International Air Transport Association

EC50 - Median effective concentration

IMDG - International Maritime Dangerous Goods

LC50 - Median lethal concentration

LD50 - Median lethal dose

LOAEL - Lowest Observed Adverse Effect Level

NOAEC - No-Observed Adverse Effect Concentration

NOAEL - No-Observed Adverse Effect Level

NOEC - No-Observed Effect Concentration

PBT - Persistent Bioaccumulative Toxic

PNEC - Predicted No-Effect Concentration

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS - Safety Data Sheet

vPvB - Very Persistent and Very Bioaccumulative

Other information

None.

Full text of H-statements:	
H302	Harmful if swallowed
H312	Harmful in contact with skin
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction



HIT-RE 500 V4, A

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS_UN_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.